

COMPACT, HIGH-PERFORMANCE
THERMOGRAPHIC CAMERA



Ceres T 640 Series

Compact and uncooled LWIR thermographic camera



COMPACT, HIGH-PERFORMANCE
THERMOGRAPHIC CAMERA

KEY FEATURES

- ◆ Compact size
- ◆ 6X SHULRURERDUGWKIUPRWD SKFSHUIRUPDEH (stability, accuracy)
- ◆ Temperature measurements up to 400°C
- ◆ Frame rate up to 60 Hz
- ◆ Low latency synchronization

The Ceres T 640 series is based upon the Dione 640 OEM thermal imaging core with 640x480 pixels and 12 μm pixel pitch. The camera provides high performance and reliability.

The Ceres T 640 camera outputs full frame images at 60 Hz via either a CameraLink or GigE Vision interface. It is designed for industrial applications requiring high precision and accuracy.

Ceres T 640 Series

EU based supplier



KEY PERFORMANCES

Image format/Pixel pitch	640 x 480 pixels / 12 μ m
Integration type	Rolling Shutter
Spectral range	8 -14 μ m
Max frame rate (full frame)	Up to 60 Hz
Power consumption	4 W (GigE); 3.5 W (CL)
Power supply voltage	DC 12 V

FUNCTIONS & INTERFACES

Digital output format	GigE; CL
Ambient operating temperature range	From +10 $^{\circ}$ C to +50 $^{\circ}$ C
Storage temperature range	From -40 $^{\circ}$ C to +85 $^{\circ}$ C
Detector NETD	<50 mK (at 30Hz, 300K, F/1)
Shock / Vibration	25g, 3ms, IEC 60068-2-27 / 2g, IEC 60068-2-6

PRODUCT SELECTOR GUIDE

XEN-000681 [Ceres T 640 GigE 50 mK (60 Hz)]	XEN-000723 [Ceres T 640 GigE 50 mK (9 Hz)]
XEN-000682 [Ceres T 640 CL 50 mK (60 Hz)]	XEN-000726 [Ceres T 640 CL 50 mK (9 Hz)]

* The camera comes with one standard option of lens and thermal calibration pack.
For more information, contact us at sales@xenics.com

sales@xenics.com



xenics.com

Xenics
Photonis Group

© Xenics. XDS027. The information furnished is believed to be accurate and reliable, but is not guaranteed and is subject to change without notice. No liability is assumed by Xenics for its use. Performance data represents typical characteristics as individual product performance may vary. Customers should verify that they have the most current Xenics product information before placing orders. No claims or warranties are made as to the application of Xenics products. Texts and pictures may not be considered as contractually binding. This document may not be reproduced, in whole or in part, without the prior written consent of Xenics.